



HIRAM

Habitat

Initial Care of an Oiled HIRAM Plank Floor - Raw Wood Effect

YOU WILL NEED:


- NATURHAUS *Performance Oil*

GENERAL:

Materials contaminated with this product generate heat during drying. Therefore, never leave flammable materials (e.g. cloths, clothing, abrasives, etc.) unattended. Immediately place them fully submerged in a container filled with water and store them for at least 3 days.

After installation, the oiled floor must be treated with Naturhaus Performance Oil to complete the protection.

The oil has a surface-densifying and water-repellent effect while remaining vapor-permeable. The resulting hard and robust surface offers high durability. In addition to resistance to grease and cleaning agents, it provides excellent resistance to abrasion, scuffing, and scratching. The finished surface is easy to clean and maintain.



PLEASE NOTE:

- Observe the safety instructions on the product
- Product, room, and floor temperature: **minimum 20 °C**
- Coverage: 50–65 m²/l (equivalent to 15–19 g/m²)
- Ensure sufficient ventilation during application and drying



APPLICATION:

1. Stir the *Performance Oil* thoroughly before use.
2. The oil is ready to use and is applied thinly by rolling, brushing, spreading, or using a single-disc machine.
3. For a *matte surface*, one film-forming coat is sufficient. If a *matte to silk-matte finish* is desired, polishing with a fine cloth is recommended. For structured surfaces, polishing is recommended, otherwise irregularities in the surface appearance may occur.
4. The wooden floor is **dust-dry after approx. 4–6 hours** and **lightly loadable after approx. 8 hours**. The surface reaches its maximum durability after 14 days. It is recommended not to cover large areas during the first 14 days. Newly oiled surfaces should only be cleaned dry during this period.

